

INSTRUCTIONS & INFORMATION



FAN KIT - CANOPY

Part Number 503370

The Canopy Fan Kit has been designed to mount to the bottom side of the canopy.

FAN KIT INSTALLATION

INSTRUCTIONS:

(Refer to illustration)

- Park tractor on a flat level surface.
- Disengage PTO and stop engine.
- Set park brake and remove key from ignition.
- Attach the Fan Bracket (item 1) to the four holes in the center and toward the front of the canopy top. Notice the multiple slots in the bracket, this allows the fan bracket to be located in numerous positions, front to back. Secure bracket with four .312-18 x .75 whiz bolts and .312-18 whiz nuts (items 11 & 12).
- With four .312 SAE washers (item 13) between fan and fan shield fasten the Canopy Fan (represented by item 3) to Fan Shield (item 2) with four .250-20 x .75 whiz bolts and .250-20 whiz nuts (items 9 & 10).
- Notice the two tabs with the round holes on the fan shield. Attach these two tabs to the inside of the two tabs on the fan bracket. Secure with two .312-18 x .75 bolts and .312-18 nylon insert nuts (items 7 & 8). Do not over tighten nuts, shield should be allowed to pivot.
- Rotate the fan shield up so that the two tabs with the square holes are inside the front of the fan bracket with the long curved slots. Insert .312 x .75 carriage bolts (item 4) into the square holes and through the curved slots. Secure with two .312 washers and .312-18 Thumb Screws (items 5 & 6).
- Install Edge Trim (item 14) on the front edge of the fan bracket (item 1).
- By loosening the thumb screws (item 6) the fan can be rotated to a desired angle. When in the desired position retighten thumb screws.
- Install Wiring Harness as shown in wiring diagram. The magnetic mount switch box can be attached to back of the canopy fan bracket (item 1).