

INSTRUCTIONS & INFORMATION



SEATBELT MOUNT KIT - ENCLOSURE W/ROPS

Kit Number 533383
for Serial # 5499999 and below

SEAT BELT INSTALLATION

A sharp knife is needed for installation.

- Place the Seatbelt Mount (item 7) next to the ROPS tube (item 9) with the bottom of the mount 2" above the center of the bend in the ROPS tube (see Fig. 2). Mark the rear cab panel fabric on each side of the machine where the seatbelt mount contacts the fabric.
- Make a 2" cut through the fabric.
- On the right side of the machine, position seatbelt mounts (items 7 & 8) around ROPS tube as shown in the Top View (Fig. 1).
- Insert a 1/2 x 1 1/4" bolt (item 1) through the back end of the seat belt mounts.
- Turn 1/2" lock nut (item 4) finger tight.
- Insert a 1/4 x 3/4" truss head bolt (item 2) through the seatbelt mounts on the front side of the ROPS tube and tighten the nut (item 3) finger tight.
- Install a 1/2 x 1 1/4" bolt (item 1) through the seatbelt retractor, flat washer (item 5) and the front end of the seat belt mounts (items 7 & 8). Turn 1/2" lock nut (item 4) finger tight.
- The retractor should be angled at about 20 degrees above horizontal.
- Tighten all the bolts and position the brackets 2" above the center of the bend in the ROPS tube.
- Install the buckle side (left) the same way.

