

INSTRUCTIONS & INFORMATION



SUSPENSION SEAT KIT – 200

Part Number 503662

Used on Model 200 Grasshopper Tractors

With Serial # 5500000 thru 6059999.

SEAT REMOVAL INSTRUCTIONS:

- Place unit on a hard level surface.
- Disengage PTO and stop engine.
- Set park brake and remove key from ignition.
- Flip seat up and disconnect seat safety switch wires.
- Remove the seat hinge pins and remove the seat. Save the whiz bolts and nuts for later use.
- Remove the seat springs.
- Remove the seat cushions and side panels from the bottom seat panel. The side panels, back panel, cushions and armrests will be reused.

SUSPENSION SEAT INSTALLATION INSTRUCTIONS:

(Refer to illustration on page 2)

- Install the rubber bumpers (item 21) in the seat spring holes and secure with 5/16-18 whiz nut (item 18).
- Set the suspension seat assembly in place, install the seat hinge pins (item 15) and secure pins with 5/16-18 whiz bolts and nuts removed earlier.
- Connect the seat safety switch wires from the tractor to the wiring adapter (item 20) and secure them in the snap clips.
- Make sure the seat latch operates correctly.
- Bolt the seat cushions and side panels, removed earlier, to the seat plate (item 1).
- Connect the seat safety switch wires from the wiring adapter (item 20) to the switch in the seat cushion.
- Be sure seat safety switch operates properly. The engine should die if the operator gets off the seat with either steering lever in or the PTO switch on.